

 **TITAN GLOBAL WHEEL**

# EXPERIENCE THE GOODYEAR ADVANTAGE



FRONT: GOODYEAR LSW1000/40R32  
REAR: GOODYEAR LSW1100/45R46

**LSW**  
Low Sidewall Technology®



[www.titanglobalwheel.co.za](http://www.titanglobalwheel.co.za)



### STANDARD FACTORY TIRES

FRONT: GOODYEAR SUPER TRACTION RADIAL 380/80R38  
 CONTACT AREA: 924"  
 FRONT AXLE WEIGHT: 13,614 LB  
 AIR PRESSURE: 15 PSI

REAR: GOODYEAR SUPER TRACTION RADIAL 480/80R50  
 CONTACT AREA: 1,444"  
 REAR AXLE WEIGHT: 16,638 LB  
 AIR PRESSURE: 8 PSI

**TOTAL CONTACT AREA: 2,368"**



### GOODYEAR LSW® EXTREME FLOTATION™ TIRES

FRONT: GOODYEAR OPTITRAC LSW1000/40R32 SINGLE  
 CONTACT AREA: 1,544"  
 FRONT AXLE WEIGHT: 12,700 LB  
 AIR PRESSURE: 10 PSI

REAR: GOODYEAR DT930 LSW1100/45R46  
 CONTACT AREA: 1,944"  
 REAR AXLE WEIGHT: 14,500 LB  
 AIR PRESSURE: 6 PSI

**TOTAL CONTACT AREA: 3,488"**

#### GOODYEAR DT930 (rear)

Size	1100/45R46
TL/TT	TL
PR/LI/Star Rating	181D
Industry Code	HF-3
Max Rated Load (lb)	18,200
Rated Inflation (psi)	17
Max Rated Speed (mph)	40
Recommended Rim (in)	38
Overall Diameter (in)	83.7
Overall Width (in)	39.5
Static Loaded Radius (in)	36.8
Rolling Circumference (in)	245
Flat Plate Contact Area (sq in)	972
Tire Weight (lb)	1,204
Tread Depth (32nd)	77



#### GOODYEAR OPTITRAC (front)

Size	1000/40R32
TL/TT	TL
PR/LI/Star Rating	180D
Industry Code	HF-3
Max Rated Load (lb)	17,600
Rated Inflation (psi)	35
Max Rated Speed (mph)	40
Recommended Rim (in)	36
Overall Diameter (in)	66.4E
Overall Width (in)	38.8E
Static Loaded Radius (in)	29.1E
Rolling Circumference (in)	194E
Flat Plate Contact Area (sq in)	772E
Tire Weight (lb)	884
Tread Depth (32nd)	79

#### CONTACT

Tel: +27 (0) 16 341 9800  
 Louis Enslin: louis@titangw.co.za

[www.titanglobalwheel.co.za](http://www.titanglobalwheel.co.za)

