

 **TITAN GLOBAL WHEEL**

# LSW THE ULTIMATE UPGRADE



- GOODYEAR EXTREME FLOTATION™**
- LSW1000/40R32 AND LSW1100/45R46
  - 20% IMPROVEMENT TO FOOTPRINT
  - UP TO 40% LOWER INFLATION PRESSURES

**LSW**<sup>®</sup>  
Low Sidewall Technology<sup>®</sup>



MADE BY TITAN<sup>®</sup>

[www.titanglobalwheel.co.za](http://www.titanglobalwheel.co.za)

# WHAT IS LSW<sup>®</sup> TECHNOLOGY?



At Titan, we have the ability to design, test and manufacture both wheels and tires for the agriculture market. Our unique position as a complete solutions provider allows us to innovate in ways other companies can't. One of these innovations is Low Sidewall Technology.

Low Sidewall (LSW<sup>®</sup>) technology features a larger rim diameter and smaller sidewall than a conventional tire, while maintaining the same outside diameter and weight load capacity. The larger rim and smaller sidewall of LSW<sup>®</sup> provides much greater stability for equipment.

## LSW<sup>®</sup> BENEFITS



**REDUCED SOIL COMPACTION**  
with ability to carry loads at 40% lower inflation pressures.



**REDUCE ROAD LOPE**  
faster, smoother transport speeds between fields.



**IMPROVED TRACTION**  
with greater stability and footprint, providing more power to the ground.



**STUBBLE-RESISTANT**  
compounding backed by warranty.



**REDUCED POWER HOP**  
with larger wheel diameter that dampens recoil in high draw-bar applications.



**AMERICAN MADE**  
All Titan and Goodyear Farm Tire products are proudly made in America.



**NATION WIDE AG SPECIALIST SUPPORT**  
You're never alone in the field with our skilled tire and wheel experts standing by to assist you.

## LSW<sup>®</sup> EQUIPPED MACHINES



**4WD AND MFWD TRACTORS**  
Whether conducting pre-emergence field work or working in between the rows, tractors experience improved transport speeds and an improved turning radius.



**COMBINES**  
LSW<sup>®</sup> tires are built to withstand the heavy loads of today's high-horsepower combines while requiring 40% less inflation pressures vs. conventional tires.



**SPRAYERS**  
As sprayer tanks continue to grow to sizes in excess of 1,300 gallons, newer technologies are becoming essential for carrying the load and reducing soil compaction. With LSW<sup>®</sup>, growers don't have to make sacrifices in ride quality and stability.

### CONTACT

Tel: +27 (0) 16 341 9800  
Louis Enslin: louis@titangw.co.za

[www.titanglobalwheel.co.za](http://www.titanglobalwheel.co.za)

 **TITAN GLOBAL WHEEL**



MADE BY TITAN